



814300M (mm)	814300A (inch)	D1 (mm)	D2 (mm)	L (mm)	 (g)	 (pcs)
41	1-5/8	68	86	115	3010	1
42		70	86	115	3080	1
	1-11/16	71	86	115	3120	1
	1-3/4	72	86	115	3200	1
46	1-13/16	74	86	125	3440	1
	1-7/8	77	86	125	3550	1
	1-15/16	78	86	125	3590	1
50		79	86	135	3840	1
	2"	80	86	135	3930	1
	2-1/16	82	86	135	4030	1
54	2-1/8	84	86	135	4130	1
55		85	86	135	4160	1
	2-3/16	86	86	135	4200	1
	2-1/4	87	86	135	4160	1
60	2-3/8	91	86	135	4370	1
	2-7/16	93	86	135	4490	1
	2-1/2	95	86	135	4630	1
65	2-9/16	97	86	145	5260	1
	2-5/8	98	86	145	5320	1
	2-11/16	101	86	145	5670	1
70	2-3/4	103	86	145	5780	1
	2-13/16	105	86	145	6000	1
	2-7/8	106	86	145	6080	1
75	2-15/16	108	86	155	6580	1
	3"	110	86	155	6850	1
80	3-1/8	116	86	165	7040	1
85		122	86	165	7420	1
90		128	86	175	9630	1
95	3-3/4	135	127	175	9750	1
	3-7/8	139	127	175	9980	1
100		140	127	185	10320	1
	4"	146	127	195	10850	1
105	4-1/8	146	127	195	10850	1
110	4-1/4	153	127	195	11500	1
115	4-1/2	160	127	195	12160	1
	4-5/8	164	127	195	13100	1
120	4-3/4	166	127	205	13680	1
125	4-7/8	173	127	205	14450	1
	5"	176	127	205	14950	1
130		180	127	205	15190	1


814300M/814300A



MAXIMUM SOCKET

MAXIMUM TORQUE



RESISTANCE TO IMPACT



814800



RETAINER : PIN

mm	175	250	330	500
inch	7"	10"	13"	20"
	8000	11400	15100	22820
	2	1	1	1